



राष्ट्रीय फैशन टेक्नालॉजी संस्थान
(वस्त्र मंत्रालय, भारत सरकार)

National Institute of Fashion Technology
Ministry of Textiles, Govt. of India
(An ISO 9001:2008 certified institute)

June 22, 2018

QUOTATION NOTICE

NIFT – Kannur invites quotation from the qualified contractors for the following civil works. Intending contractors who have GST registration may submit the quotation in the following works and submit the same by post/courier/ by hand so as to reach the National Institute of Fashion Technology, NIFT campus, Mangattuparamba, Kannur – 670562 on or before 27.06.2018, 05.00 PM.

Sl. No.	Name of Work	Last date for receipt of duly filled in quotations
1.	Providing Toilet & LP gas storage room near Mess In NIFT Kannur.	27.06.2018, 05:00 PM

Note: Quotation schedule will be given by the NIFT to the contractors free of cost on request up to 27.06.2018, 1.00 PM

Terms & Conditions

1. Rates inclusive of all taxes, duties, transportation, loading, unloading charges etc.,
2. The work should be completed within 30 days of issue of work order.
3. Attach the proof of PAN Card and GST Registration No.
4. Payments will be made within 15 days against satisfactory completion of the work and acceptance of the items by competent authority.

Nagesan
22/6/18
ASSISTANT DIRECTOR

Copy for display in the notice board as per list:

1. Municipal office, Anthoor.
2. Govt. Engineering Collage, Kannur.
3. Village office, Morazha.
4. NIFT Kannur

A Premier Institute of Design, Management & Technology
Set up under an Act of Parliament

NIFT Campus, Dharmasala, Kanool (P.O.), Kalliasseri, Kannur, Kerala - 670 562
t + 0497 2784780 to + 0497 2784786 | f + 0497 2784785 | e info.kannur@nift.ac.in

www.nift.ac.in/kannur

Providing Toilet and LP Gas storage room near mess in NIFT Kannur						
SlNo	ItemNo	Description	Quantity	Unit	Rate in Figures & Words	Amount
1		Earth work in excavation by mechanical means (Hydraulic excavator) /manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.				
		All kinds of soil	4m³			
2	50.6.7.1	Laterate masonry with neatly dressed laterate stone of size 40x20x15cm or nearest size in cement mortar 1:6 for foundation and basement including all cost of materials, labour charges etc.	4.60m³			
3	50.6.7.2	Laterate masonry with neatly dressed laterate stone of size 40x20x15cm or nearest size in cement mortar 1:6 for super structure above plinth level up to floor two level including all cost of materials, labour charges etc.	3.70m³			
4	5.3	Reinforced cement concrete work in beams, suspended floors, roofs, having slope up to 150 landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases up to floor five level excluding the cost of centering, shuttering, finishing and reinforcement, with 1:1.5:3 (1 cement : 1.5 coarse sand (Zone III) : 3 graded stone aggregate 20 mm nominal size).	1m³			
5	5.22.6	Steel reinforcement for R.C.C work including straightening, cutting, bending, placing in position and binding all complete upto plinth level Thermo - Mechanically Treated bars	80Kg			
6	5.9.5	Centering and shuttering including strutting, etc. and removal of form for: Lintels, beams, plinth beams, girders bressumers and cantilevers	5.40m²			
7	13.1.1	12 mm cement plaster of mix: 1:4 (1 cement : 4 fine sand including all cost conveyance and all labour charge	75m²			
8	9.48.1	Providing and fixing M.S. Grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete.	370Kg			
9	5.1.3	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level: 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	0.70m³			
10	12.1.3	Providing corrugate G.S. sheet roofing including vertical/ curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal / vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. 0.63 mm thick with zinc coating not less than 275 gm/m2	29m²			
11	12.4.2	Providing ridges or hips width 60 cm overall width plain G.S. sheet fixed with polymer coated J or L hooks, bolts and nuts 8 mm dia G.I. limpet and bitumen washers complete. 0.63 mm thick with zinc coating not less than 275 gm/m2	6.00m			
12	10.16.1	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished welded type tubes	150Kg			
13	13.61.1	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work	25m²			
14	13.43.1	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer	61m²			
15	13.47.1	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade: New work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	61m²			

16	9.117.2	Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ± 1 mm), with wall thickness 2.0mm (± 0.2 mm), corners of the door frame to be jointed with galvanized brackets and stainless steel screws, joints mitred and plastic welded. The hinge side vertical of the frames reinforced by galvanized M.S. tube of size 19 x 19 mm and 1 mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineer-in-charge				
			4.80m			
17	9.118.1	Providing and fixing to existing door frames 24 mm thick factory made PVC door shutters made of styles and rails of a uPVC hollow section of size 59x24 mm and wall thickness 2 mm (± 0.2 mm) with inbuilt edging on both sides. The styles and rails mitred and joint at the corners by means of M.S. galvanised/plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 20x20 mm and 1 mm (± 0.1 mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x24 mm and 2 mm (± 0.2 mm) wall thickness, fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (± 0.1 mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge (For W.C. and bathroom door shutter).				
			1.41m ²			
18	11.37A	Providing and fixing 1st quality ceramic glazed floor tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete				
			30m ²			
19	17.2.1	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:				
		W.C. pan with ISI marked white solid plastic seat and lid				
			1No			
20	50.18.9.9.1	Providing and fixing PVC pipes including jointing of pipes with one step PVC solvent cement, trenching, refilling & testing of Joints complete as per direction of engineer in charge. 110 mm dia 6Kgf/cm ²				
			8m			
21	50.18.9.6.2	Providing and fixing PVC pipes including jointing of pipes with one step PVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge. 50 mm dia 6 Kgf/cm ²				
			8m			
22	50.18.9.2.2	Providing and fixing PVC pipes including of pipes with one step PVC solvent cement, trenching, refilling & testing of joints complete as per direction of Engineer in Charge. 20 mm dia 10 Kgf/cm ²				
			15m			
23	50.17.1.4	Supplying and fixing CP Health faucet good quality including cost of materials and labour charges etc. complete as per the direction of site engineer-in-charge.				
			1No			
24	50.17.1.3	Supplying and fixing CP Towel rod 60cm or nearest available length including cost of materials and labour charges etc complete as per the direction of site Engineer-in-charge.				
			1NO			
25	50.17.1.1	Supplying and fixing Stainless steel soap dish including cost of materials and labour charges etc complete as per the direction of site Engineer-in-charge.				
			1No			
26	18.15.1	Providing and fixing brass bib cock of approved quality : 15 mm nominal bore				
			2No			
27	18.18.2	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 20 mm nominal bore				
			2No			
		Total in figures				
		Total in words				

Name & Signature of the Contractor
(Phone No & Address)
G S T No: