

## राष्ट्रीय फैशन प्रौद्योगिकी संस्थान

सांविधिक संस्थान निफ्ट अधिनियम 2006 वस्त्र मंत्रालय, भारत सरकार

## NATIONAL INSTITUTE OF FASHION TECHNOLOGY

A Statutory Institute under the NIFT Act 2006 Ministry of Textiles, Government of India

4790(3)/Bldg/Artificial Grass Turf/2019/ 多子

दिनांक: 26.10.2023

## भाव पत्रक / Rate Enquiry Letter

राष्ट्रीय फैशन प्रौद्योगिकी संस्थान (निफ्ट) मुंबई द्वारा निम्नलिखित कार्य के लिए मोहरबंद निविदाएँ आमंत्रित करता हैं। निफ्ट, बिना कोई कारण बताए निम्नतम या सभी निविदाओं को स्वीकार या अस्वीकार करने का अधिकार सुरक्षित रखता है।

Sealed Quotations are hereby invited by NIFT Centre, Mumbai for the following work. The undersigned reserves the right to accept or reject the lowest or all the quotations without assigning any reasons.

कार्य का नाम: निफ्ट परिसर प्लॉट संख्या -15, सेक्टर-04, खारघर नवी मुंबई के रंग-मंच, खेल के मैदान और अन्य क्षेत्र में बाहरी रंग-रोगन कार्य और विविध मरम्मत कार्य ।

Name of work: External painting work and miscellaneous repair work in Stage area, play ground and other area of NIFT campus Plot No. 15, Sector 04, Kharghar Navi Mumbai.

क्रम संख्या	कार्य का विवरण	मात्रक	मात्रा	दर (रुपये)	राशि
1	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	Sqm	15	(044)	(रुपये)
2	Repair to plaster of thickness 12mm to 20 mm in patches of area 2.5 sum and under, including cutting the patch in proper shape, raking out joints and preparing plastering the wall surface with white cement based polymer modified self curing mortar, including disposal of rubbish, all complete as per the direction of Engineer-In-Charge.	Sqm	15		
3	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade				

Seal and signature of the Agency

Date:

Joint Director

डिज़ाइन, मैनेजमेंट और प्रौद्योगिकी का सर्वश्रेष्ठ संस्थान A Premier Institute of Design, Management and Technology

Page 1 of 5

(An ISO 9001: 2015 certified institute)

निफ़्ट कैम्पस, प्लॉट नं. 15, सेक्टर 4, खारघर, नवी मुंबई - 410210, महाराष्ट्र NIFT Campus, Plot No.15, Sector 4, Kharghar, Navi Mumbai - 410210, Maharashtra © + 91 022 27747000 | + 91 022 27747100 | + 91 022 27745386 | e: nift.mumbai@nift.ac.in

www nift ac in



3.1	Old work (Two or more coats applied @ 1.43 ltr/ 10 sqm) over existing paint surface & Provide primer touch up if required as per direction incharge.	Sqm	700	
4	Finishing with Epoxy paint (two or more coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete.	•		
4.1	On steel work	Sqm	5	
4.2	On concrete work	Sqm	17.5	
5	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:			
5.1	Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture.	Sqm	115	
6	Removing of existing damaged doors and Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-In- Charge.			
6.1	30 mm thick	Sqm	7.2	
7	Carefully removing of existing aluminum composite panel sheet without damging of frame and Providing &	Sq Ft	85	

Seal and signature of the Agency

Date:

Joint Director

Page **2** of **5** 



Fixing of 2mm this last				
over a existing frame work of required shade and fixing it with S.S. L- Patti of size 25mm x25 mm.	t g			
machine, Clean the area thoroughly so that it is free from dust and loose particles, Apply a self-priming coat [1:1 dilution with water] of SmartCare Textured Crack Filler over crack edges and allow it to dry for 1-2 hrs, Apply first coat of undiluted SmartCare Textured Crack Filler on the crack using spatula or putty knife, Press the paste firmly into the crack to ensure full contact with the surface and level the surface, Spread SmartCare Textured Crack Filler up to at least 3 cm on either side of the crack for better adhesion, Apply in consecutive perpendicular layers to avoid leaving air pockets, Allow it to dry for a minimum 6 hours, Apply the second undiluted coat in the same manner, apply the one coat exterior primer and two coat of exterior paint as per approved quality and matching colour shad, including cost of crack filler, cost of paint, cost of tools and tackles, cost of Spiderman painting safety kit/painting jula, etc., work should carry out as per direction of Engineer in charge.		50		
Providing & Fixing of new wheel of sliding partition over existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing hanging channel section.	Job	1		
Carefully Removing of Damaged/Non working double action hydraulic floor spring and without damaging of existing glass door and Providing and fixing double action hydraulic floor spring of approved brand and manufacture, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 120 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer box with slide plate With stainless steel cover plate	Nos	1		
	Exterior wall crack fill work: Open the crack and widen it to form a 'V' shaped groove with help of a cutting machine, Clean the area thoroughly so that it is free from dust and loose particles, Apply a self-priming coat [1:1 dilution with water] of SmartCare Textured Crack Filler over crack edges and allow it to dry for 1-2 hrs, Apply first coat of undiluted SmartCare Textured Crack Filler on the crack using spatula or putty knife, Press the paste firmly into the crack to ensure full contact with the surface and level the surface, Spread SmartCare Textured Crack Filler up to at least 3 cm on either side of the crack for better adhesion, Apply in consecutive perpendicular layers to avoid leaving air pockets, Allow it to dry for a minimum 6 hours, Apply the second undiluted coat in the same manner, apply the one coat exterior primer and two coat of exterior paint as per approved quality and matching colour shad, including cost of crack filler, cost of paint, cost of tools and tackles, cost of Spiderman painting safety kit/painting jula, etc., work should carry out as per direction of Engineer in charge.  Providing & Fixing of new wheel of sliding partition over existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing hanging channel section.  Carefully Removing of Damaged/Non working double action hydraulic floor spring and without damaging of existing glass door and Providing and fixing double action hydraulic floor spring of approved brand and manufacture, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 120 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer	Exterior wall crack fill work: Open the crack and widen it to form a 'V' shaped groove with help of a cutting machine, Clean the area thoroughly so that it is free from dust and loose particles, Apply a self-priming coat [1:1 dilution with water] of SmartCare Textured Crack Filler over crack edges and allow it to dry for 1-2 hrs, Apply first coat of undiluted SmartCare Textured Crack Filler on the crack using spatula or putty knife, Press the paste firmly into the crack to ensure full contact with the surface and level the surface, Spread SmartCare Textured Crack Filler up to at least 3 cm on either side of the crack for better adhesion, Apply in consecutive perpendicular layers to avoid leaving air pockets, Allow it to dry for a minimum 6 hours, Apply the second undiluted coat in the same manner, apply the one coat exterior primer and two coat of exterior paint as per approved quality and matching colour shad, including cost of crack filler, cost of paint, cost of tools and tackles, cost of Spiderman painting safety kit/painting jula, etc., work should carry out as per direction of Engineer in charge.  Providing & Fixing of new wheel of sliding partition over existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing lob leaction hydraulic floor spring and without damaging of existing glass door and Providing and fixing double action hydraulic floor spring of approved brand and manufacture, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 120 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer.	Exterior wall crack fill work: Open the crack and widen it to form a 'V' shaped groove with help of a cutting machine, Clean the area thoroughly so that it is free from dust and loose particles, Apply a self-priming coat [1:1] dilution with water] of SmartCare Textured Crack Filler over crack edges and allow it to dry for 1-2 hrs, Apply first coat of undiluted SmartCare Textured Crack Filler on the crack using spatula or putty knife, Press the paste firmly into the crack to ensure full contact with the surface and level the surface, Spread SmartCare Textured Crack Filler up to at least 3 cm on either side of the crack for better adhesion, Apply in consecutive perpendicular layers to avoid leaving air pockets, Allow it to dry for a minimum 6 hours, Apply the second undiluted coat in the same manner, apply the one coat exterior primer and two coat of exterior paint as per approved quality and matching colour shad, including cost of crack filler, cost of paint, cost of tools and tackles, cost of Spiderman painting safety kit/painting jula, etc., work should carry out as per direction of Engineer in charge.  Providing & Fixing of new wheel of sliding partition over existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing hanging channel section.  Carefully Removing of Damaged/Non working double action hydraulic floor spring and without damaging of existing glass door and Providing and fixing double action hydraulic floor spring of approved brand and manufacture, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 120 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer.	it with S.S. L- Patti of size 25mm x25 mm .  Exterior wall crack fill work: Open the crack and widen it to form a 'V' shaped groove with help of a cutting machine, Clean the area thoroughly so that it is free from dust and loose particles, Apply a self-priming coat [1:1 dilution with water] of SmartCare Textured Crack Filler over crack edges and allow it to dry for 1-2 hrs, Apply first coat of undiluted SmartCare Textured Crack Filler on the crack using spatula or putty knife, Press the paste firmly into the crack to ensure full contact with the surface and level the surface, Spread SmartCare Textured Crack Filler up to at least 3 cm on either side of the crack for better adhesion, Apply in consecutive perpendicular layers to avoid leaving air pockets, Allow it to dry for a minimum 6 hours, Apply the second undiluted coat in the same manner, apply the one coat exterior primer and two coat of exterior paint as per approved quality and matching colour shad, including cost of crack filler, cost of paint, cost of tools and tackles, cost of Spiderman painting safety kit/painting jula, etc., work should carry out as per direction of Engineer in charge.  Providing & Fixing of new wheel of silding partition over existing hanging channel section including servicing, greasing of all rollers and supportive elements of existing hanging channel section.  Carefully Removing of Damaged/Non working double action hydraulic floor spring and without damaging of existing glass door and Providing and fixing double action hydraulic floor spring of approved brand and manufacture, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 120 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer.

Seal and signature of the Agency

Date:

Joint Director

Page 3 of 5



## नियम एवं शर्तें / Terms & Conditions:

- 1) मोहरबंद भाव पत्रक जमा करने की **अंतिम तिथि 01 नवम्बर 2023 को अपराह: 3 बजे** तक है | Last date of receipt of sealed Quotation is **01/11/2023 upto 3.00 pm**.
- 2) उद्धृत दरें 90 दिनों के लिए मान्य होंगी। The quoted rates must be valid for 90 days.
- 3) एजेंसी को कार्य करने के लिए निफ्ट अधिकारी द्वारा स्वीकृत सामग्री का उपयोग करना हैं। The work shall be executed with material as approved by NIFT official.
- 4) कार्य के मूल्य /दर ,उपयोग में आने वाले सामान ,किराया ,परिश्रम और उपयुक्त कर सहित उद्धृत करने चाहिए ,जीएसटी के आलावा अलग से किसी भी राशि का भुगतान नहीं किया जाएगा| The quoted rates will be inclusive of cost of all material requires, transportation, labour and taxes as applicable, nothing shall be paid extra except GST.
- 5) कोई अग्रिम भुगतान नहीं किया जाएगा। No advance payment will be made.
- 6) एजेंसी को कार्य ,कार्य आदेश प्राप्ति से 20 दिनों तक पूरा करना होगा। कार्य पूरा करने में देरी के लिए 250/-प्रतिदिन की दर से जुर्माना लगाया जाएगा। The Agency has to complete the work within 20 days after receipt of work order. panelty @ 250/per day will be imposed for delay in completion of work.
- 7) एजेंसी को सुरक्षा नियमों को ध्यान में रखकर कार्य का निष्पादन करना चाहिए और वह अपने कामगारों की सुरक्षा के लिए स्वयं जिम्मेवार होगी।
  The agency should execute the work keeping safety rules in mind and will be responsible for the safety of its workers.
- 8) कार्य करने समाप्ति पर कार्य की मात्रा भिन्न हो सकती है इसलिए कार्य का भुगतान वास्तविक पैमाइश के आधार पर बिल और पैमाइश जमा करने पर किया जाएगा।

Seal and signature of the Agency

Date:

Joint Director

Page 4 of 5



Quantity of work may vary at the time of execution, hence payment shall be made on actual basis on submission of bill with measurementsheet .

- 9) कार्य में किसी भी प्रकार की त्रुटी होने पर निफ्ट के अनुसार एजेंसी को कार्य की मरम्मत करनी होगी | In lieu of any defect, the work shall be repaired by the agency if NIFT desires so.
- 10) किसी भी विवाद के मामले में न्यायालय का न्यायिक अधिकार क्षेत्र नवी मुंबई होगा। In case of any dispute the Jurisdiction of Court will be Navi Mumbai.
- 11) कार्य पूरा होने के बाद साइट को साफ किया जाना चाहिए और परिसर से किसी भी बेकार सामग्री/सामान/ विघटित सामग्री/न उपयोगी वस्तू को हटा दिया जाना चाहिए और उसे बिना किसी अतिरिक्त लागत/मुफ्त लागत साथ और इस न उपयोगी वस्तू को स्थानीय नगरपालिका मैदान में डंप किया जाना चाहिए।

After completion of the work the site should be cleaned and any waste materials/ stuffs/rabbit/muck to be removed from the campus and same should be dump at local municipal ground without additional cost/free of the cost.

प्रितस्पर्धी मूल्य/दरों को कोट करने से पूर्व, कार्य और स्थल के भौतिक मूल्यांकन और पैमाइश के बारे में स्पष्टीकरण के लिए (यदि कोई हो तो), एजेंसी निफ्ट के अधिकारी से कार्यालय समय के दौरान संपर्क कर सकती है।

The Agency must visit the campus and Contact to NIFT's Official for clarifications about physical assessment of area/work to be furnished and about measurement etc. before quoting the competitive rates.

जीएसटी मापदंडो के अनुसार लागू होगा / GST will be applicable as per norms

क्रम संख्या	पंजीकरण का विवरण Details of Registration	पंजीकरण संख्या Registration No.
1.	जी एस टी / GST	No.
2.	पैन कार्ड / Pan Card	

एजेंसी का नाम और पता		
मैसर्स,		- vsham)
· · · · · · · · · · · · · · · · · · ·		संयुक्त निदेशक
		निफ्ट मुंबई
द्रभाष न.		- /
दिनांक:		
Seal and signature of the Agency	Date:	Joint Director
		Page <b>5</b> of <b>5</b>